



Nitocote® Putty

High quality ready to-use putty

Uses

Nitocote Putty is a white ready-to-use putty for fairing and smoothing plastered and fairface concrete surfaces. In addition to that, it can be used for filling hairline cracks to give a smooth and high quality surface ready for application for all kinds of paints.

Advantages

- Smooth surface
- Good Coverage for all types of voids
- Rapid drying
- Easy to apply
- Excellent bonding to moist building surface
- Ability to apply at relatively high thickness.

Description

Ready to use white paste on most building surfaces. It gives high quality, even surface for painting. Nitocote Putty is specifically manufactured for the painter.

Technical Support

Fosroc offers a comprehensive range of high performance, high quality repair, maintenance and construction products. In addition, Fosroc offers a technical support package to specifiers, end-users and contractors, as well as on-site technical assistance in locations all over the world.

Properties

Curing characteristics at 30°C

Color	White
Density	1.70 kg/litre

Instructions for use

Surface preparation

Ensure that dust, dirt and foreign matter is brushed away. Ridges and form oil must also be removed.

Priming

To stabilise a surface which shows signs of dusting or flaking, the use of a separate primer is recommended.

Consult your local Fosroc office for the suitable primer.

Application

Apply Nitocote Putty in a thin even layer, if the area under repair requires a thick coat than apply several thin layers, allowing each layer to dry before adding the next.

Lightly sandpaper over the dry final surface before painting preferably within 24 hours of application.

Cleaning

Nitocote Putty should be removed from tools and equipment with water.

Estimating

Supply

Nitocote Putty 5 and 25 kg. bags

Coverage

Nitocote Putty 1.7 kg/m²/1mm thickness

Actual coverage rate is approximate, and will be wholly dependent upon the general substrate condition. It is recommended therefore, that site trials over a typical area are conducted to determine the likely usage / coverage rates for a particular substrate.

Storage

Shelf Life

Nitocote Putty has a shelf life of 12 months; if kept in a dry environment in its original, unopened packing. If stored in conditions of high humidity and / or temperature, the shelf life may be reduced to as little as 6 months.

Precautions

Health and Safety

Nitocote Putty does not fall into the hazard classifications. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water.

Fire

Nitocote Putty is water based and non-flammable.

Nitocote® Putty

Additional Information

Fosroc manufactures a wide range of complementary products which include:

- waterproofing membranes & waterstops
- joint sealants and filler boards
- cementitious and epoxy grouts
- specialised flooring materials

Fosroc additionally offers a comprehensive package of products specially designed for a repair and refurbishment of damaged concrete. Fosroc's Systematic Approach to concrete repair features the following:

- hand-placed repair mortars
- spray grade repair mortars
- fluid micro-concretes
- chemically resistant epoxy mortars
- anti-carbonation / anti-chloride protective coatings
- chemical and abrasion resistant coatings

For further information on any of the above, please consult your local Fosroc office.

® Denotes the trademark of Fosroc International Limited

Important note :

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products whether or not in accordance with any advice, specification, recommendation or information given by it.

telephone	fax	e-mail
++91 80-22240018/120	++91 80-22233474	india@fosroc.com



Fosroc Chemicals (India) Pvt. Ltd.

Head Office

111/3, Hafeeza Chamber II Floor,
K H Road, PBNNo. 2744, Bangalore 560027

www.fosroc.com

Regional Offices

Bangalore

Shankar House, IV Floor
1 & 18, RMV Extension
Bangalore 560 080
Ph:080-2361 3161/2361 2004
Fax : 080-2361 7454
email: Bangalore@fosroc.com

Mumbai

208/209, Persepolis
Sector 17, Vashi
Navi Mumbai 400 703
Ph:022-2789 6412/14
Fax: 022 - 2789 6413
email:Mumbai@fosroc.com

Delhi

First floor,1/2 East Patel Nagar
Opp: Vivek Cinema, Main Patel Rd
New Delhi 110 008
Ph:011-25884903/4
Fax: 011- 25884422
email:Delhi@fosroc.com

Kolkata

30/B Jodhpur Park
Ground Floor
Kolkata 700 068
Ph: 033 2472 5482
Fax: 033-2472 9921
email:Kolkata@fosroc.com

●Ahmedabad : (079) 26762799 ●Ankleshwar :(02646) 220704/224687 ●Bhubaneshwar : (0674) 2521176 ● Chennai (044) 24899949/24853383
●Chandigarh : (0172) 2639360 ● Cochin : (0484) 2356668 ●Coimbatore : (0422) 2472966 ●Goa : (0832) 2542465 ●Guwahati (0361) 2548793
●Hyderabad : (040) 27662324/27662425 ● Hubli (0836) 3402597 ●Indore : (0731) 504339/5061477 ● Jaipur : (0141) 2235349 ● Lucknow :(0522)
22239044 ● Nagercoil (04652) 2224849 ● Mangalore: (0824) 22272234 ● Visakhapatnam : (0891) 2564850

INDIA/2004/449/A

